## Mandate M/124

**CReatE** 

## MANDATE TO CEN/CENELEC

## CONCERNING THE EXECUTION OF STANDARDISATION WORK

FOR HARMONIZED STANDARDS ON

## ROAD CONSTRUCTION PRODUCTS

RELATED TO THE FOLLOWING END USES:

01/33 Floor beds (including suspended ground floors), roads and other trafficked areas 13/33 Floor finishes

**Top** 

In order to fulfill the provisions of article 7.1 of the CPD the present mandate has been structured in the following way:

### **Foreword**

Chapter I: Grounds. General conditions within the framework of the CPD.

<u>Chapter II</u>: Execution of the mandate. Conditions regarding the programming, development and execution of the standardisation work.

<u>Chapter III</u>: Harmonised standards. Conditions regarding the content and the presentation of the harmonised standards.

Annex 1

Annex 2

Annex 3

Annex 4

# **FOREWORD**

**Top** 

This mandate is issued by the Commission to CEN/CENELEC within the context of the Council Directive of 21 December, 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to construction products (89/106/EEC), hereafter referred to as "the Directive" or "the CPD".

One of the aims of the Directive being the removal of technical barriers to trade in the construction field, in so far as they cannot be removed by means of mutual recognition among Member States, it seems appropriate that standardisation mandates cover, at least during a first phase of the mandating programme, construction products likely to be subject to technical barriers to trade.

Mandate M/124 Page 2 sur 16

This mandate is intended to lay down provisions for the development and the quality of harmonised European standards in order, on the one hand, to make "approximation" of national laws, regulations and administrative provisions (hereafter referred to as "regulations") possible and, on the other hand, to allow products conforming to to them to be presumed to be fit for their intended use, as defined in the Directive.

In this respect, this mandate takes account of the basic principles prevailing in the regulations of Member States, particularly those described in chapters 3 and 4.2 of the Interpretative documents, to which standardisers must refer. As stated by the Directive, the responsibility Member States have for construction works on their territory remains unchanged.

In order to fulfil the provisions of article 7.1 of the CPD the present mandate has been structured in the following way:

Chapter I Grounds. General conditions within the framework of the CPD.

Chapter II Execution of the mandate. Conditions regarding the programming, development and execution of the standardisation work.

Chapter III Harmonised standards. Conditions regarding the content and the presentation of the harmonised standards.

# **CHAPTER I**

## **GROUNDS**

Top

- 1. This mandate falls within the framework of the general policy of the Commission with respect to technical harmonisation and standardisation, as well as within the scope of the Directive. It replaces any previous mandate on the same products formerly issued on a provisional base by the Commission.
- 2. This mandate is based on article 7 of the Directive and has taken into consideration the Interpretative Documents that serve as reference for the establishment of the harmonised standards (see article 12 of the Directive). It serves to ensure the quality of the harmonised standards for products, always with reference to the state of the art, with particular reference to the fitness of the products listed in annex 1 intended to be used in FLOOR BEDS (INCLUDING SUSPENDED GROUND FLOORS), ROADS AND OTHER TRAFFICKED AREAS and FLOOR FINISHES, enabling the works to satisfy the essential requirements set out in annex 1 of the Directive, provided that barriers to trade in these products exist and that the products fall within the scope of article 2.1 of the Directive;
- 3. Levels or classes of requirements for the works are under the responsibility of Member States and are not covered by the present mandate. As a consequence, they are not expected to be defined in the harmonised standard.
- 4. Levels or classes of requirements for the products may be determined either in the Interpretative Documents or according to the procedure provided for in article 20 (2) of the Directive. In either case, where levels or classes of requirements for products are determined, guidance is given in <u>Annex 3</u> to this mandate. This is not the case for classes of convenience, which are classes of product performances developed as a means of convenience for specifiers, manufacturers and purchasers. Such classes of convenience are not covered by the present mandate and should not be defined within the harmonised standard. Nevertheless, the results of the determination of the product characteristics may be expressed using classes of convenience introduced by European standards. Articles 3.2 and 6.3 of CPD do not apply to such classes.
- 5. The harmonised standards resulting from this mandate must allow for products to comply with them even where performance does not need to be determined for a certain characteristic because at least one Member State has no legal requirement at all for such characteristic. Declaration of performance for such a characteristic, in this case, must not be imposed on the manufacturer if he does not wish to declare it.
- Indications regarding the documents which should be taken into account to inform standardisers and
  manufacturers on national and harmonised legislation on substances classified as dangerous are given in Annex
  4

Mandate M/124

## **CHAPTER II**

## **EXECUTION OF THE MANDATE**

Top

CEN/CENELEC will present the Commission with a detailed work programme, at the latest, three months after approval of 83/189 Committee.

The work programme should identify clearly the list of harmonised standards to be developed. For each harmonised standard it should:

- indicate the name(s) of the product(s) to be covered;
- define the characteristics, durability aspects, intended uses and the forms and materials to be covered (in accordance with Annexes 1, 2 and 3 of this mandate);
- attach the list of supporting documents (e.g. work items on test methods, ...);
- justify the timetable foreseen for its finalisation; and
- identify the Technical Committee(s) responsible for the work.

Clear differentiation should be made between the item to become the harmonised standard for the product and the items to be used as supporting documents.

When a supporting test standard for one characteristic does not exist or is not in the work programme of the TC, a clear statement should be presented indicating whether CEN is able to produce one or not.

Any proposals for the addition of products, intended uses and materials and forms not included in the mandate but considered relevant by the TC should be presented separately from the work programme for further analysis by the Commission services. Standards prepared for products outside this mandate will not achieve the status of harmonised standards. In addition to the provisions of article 4.1 of the CPD, it must be taken into account that all the products included in the mandate have a system of attestation of conformity in accordance with the relevant Decision of the Commission; those products not included have not.

Any proposal for the addition of characteristics and durability aspects not included in the mandate but considered relevant by the TC should be proposed in a special chapter of the work programme for further analysis by the Commission services.

Where a classification system of the product performances is envisaged in <u>Annex 3</u> of the present mandate, CEN/CENELEC are requested to make an appropriate proposal for its implementation.

CEN/TCs must give a technical answer for the determination of the characteristics of the mandate taking into account the conditions stated below; test methods suggested must be directly related to the relevant required characteristic and must not make reference to determination methods for characteristics not required by the mandate. Durability requirements should be dealt with in the framework provided by the state of the art at present.

Reference to test/calculation methods must be in accordance with the harmonisation aimed at. In general, only one method should be referred to for the determination of each characteristic, for a given product or family of products.

If, however, for a product or family of products because of justifiable reasons, more than one method is to be referred to for the determination of the same characteristic, the situation must be justified. In this case all referenced methods should be linked by the conjunction "or" and an indication of application should be given.

In any other case, two or more test/calculation methods for the determination of one characteristic can be accepted only if a correlation between them exists or can be developed. The relevant harmonised product standard must then select one of them as the method of reference.

Testing and/or calculation methods shall have, whenever possible, a horizontal character covering the widest possible range of products

Mandate M/124 Page 4 sur 16

Within the work programme, CEN/CENELEC will also specify those cases where the performance-based approach will not be followed in the harmonised standard and will give the relevant justification.

After examination of the work programme and consultations with CEN/CENELEC, the Commission services will endorse the timetable and the list of standards or parts of standards which meet the terms of this mandate and which will be recognised as harmonised or supporting standards.

The terms of reference of this mandate may be subject to modification or addition, if necessary. Acceptance of the work programme by the Commission services does not imply acceptance of all the WIs listed as supporting standards. TCs will need to demonstrate the direct link between WIs and the needs for harmonisation of the products, intended uses and characteristics given in the mandate. Nor does acceptance exclude the possibility for further WIs to be added by CEN, in order to fully respond to the terms of the mandate

Representatives of the authorities responsible for national regulations have the right and shall be able to participate in the activities of CEN/CENELEC through their national delegations and to present their points of view at all stages of the drafting process of the harmonised standards.

The Commission may participate in standardisation activities as observer and has the right to receive all relevant documents.

CEN/CENELEC will immediately inform the Commission of any problem relating to the carrying out of the mandate and will present an annual progress report on work within the framework of the mandate.

The progress report will include a description of work carried out and information on any difficulties being met, whether political or technical, with particular reference to those that might lead the authorities of a Member State to raise objections or to resort to article 5.1 of the Directive.

The progress report will be accompanied by the latest drafts of each standard under the mandate and by updated reports on any subcontracted work.

Acceptance of this mandate by CEN/CENELEC will initiate the standstill procedure referred to in article 7 of Council Directive 83/189/EEC of 28 March 1983 modified by Council Directive 88/182/EEC of 22 March 1988 and the European Parliament and the Council Directive 94/10/EC of 23 March 1994.

Acceptance of this mandate by CEN/CENELEC can take place only after the work programme has been endorsed by the Commission services.

CEN/CENELEC will develop the draft harmonised European standards and of the relevant supporting standards on the basis of the work programme and will inform the Commission in good time that the draft is being circulated for public comment.

CEN/CENELEC will present the final drafts of the harmonised European standards and of the relevant supporting standards to the Commission services for confirmation of compliance with this mandate at the latest in accordance with the timetable agreed between CEN/CENELEC and the Commission and referred to in point II.2.d).

CEN/CENELEC members will publish the standards transposing the harmonised European standards at the latest 6 months after a positive vote in CEN/CENELEC. National standards covering the same scope will continue to be applicable until the date agreed between CEN/CENELEC and the Commission in accordance with point II.2.d)

## **CHAPTER III**

Top

## HARMONISED STANDARDS

Harmonised standards shall be prepared to allow those products listed in <u>Annexes 1</u> and <u>2</u> to be able to demonstrate the satisfaction of the essential requirements. One of the purposes of the Directive being to remove barriers to trade,

the standards deriving from it will therefore be expressed, as far as practicable in product performance terms (art. 7.2 of the Directive), having regard to the Interpretative Documents.

The harmonised standard will contain:

A detailed scope and field of application

- A detailed description of the product or family of products covered and the relevant intended uses of the different products;
- The definition of the characteristics of the products listed in <u>Annex 2</u> of the mandate (expressed in performance terms, as far as practicable) that are relevant to the satisfaction of the essential requirements;
- The methods (calculation, test methods or others) or a reference to a standard containing the methods for the determination of such characteristics;
- Guidance on the characteristics that have to be stated within the labelling that will accompany the CE marking (depending on the intended use of the product) and on the way of expressing the determined values of these characteristics;
- The classification system and the levels for the above values of characteristics, if required by the mandate;
- The system for attestation of conformity as required in <u>annex 3</u> of the mandate and the corresponding specific provisions for the evaluation of conformity.

A minimum or a maximum level of a given characteristic that has to be met by the family of products or a product may be identified by the harmonised standard only if required by agreement of Member States expressed by positive vote under the procedure of article 20.

As far as possible, each standard will make reference to performances common to other standards developed under mandate and which constitutes a cohesive and compatible group of harmonised European standards developed in parallel. CEN/CENELEC shall ensure consistency within the whole package.

A producer not wishing to meet a non-mandated European standard will be able to use the CE marking on his product by referring only to the relevant harmonised standard. On the other hand, if a non-mandated standard includes the entire content of the harmonised standard, compliance with the former standard will also give a presumption of conformity to the harmonised standard and will enable the bearing of the CE marking.

In the latter case, an appropriate system should be established in the European standard in order to clearly distinguish the CPD-related content from the remaining part of the standard.

Harmonised standards must permit construction products which allow works to meet the essential requirements and which are produced and used lawfully in accordance with technical traditions warranted by local climatological and other conditions to continue to be placed on the market.

The essential requirements being expressed in terms of performance of the works, the characteristics of the products should be also expressed in terms of performance so that, in referring to the harmonised European standards, the regulations may "approximate" evolving in terms of "performance requirements". As far as practicable and depending on the intended use mentioned in the annexes of this mandate, the standard shall include a definition of the durability in term of performance of the declared values of the product characteristics as well as suitable methods for its evaluation against the actions listed in <u>Annex 2</u>. If the durability is expressed in terms of classes of periods, articles 3.2 and 6.3 of the CPD will not apply.

The relevant systems for attestation of conformity, according to Article 13.3 and Annex III of the Directive, are listed in <u>annex 3</u>. For the establishment of the corresponding specific provisions of evaluations of conformity, the harmonised standard will take into account:

- the different intended uses of the product mentioned in the annexes of this mandate and, if any, the different levels or classes of performance;
- cases of individual (non series) production according to Article 13.5 of the Directive;
- the recommendations of paragraph 3 of Annex 3

The label accompanying the CE marking will list all the characteristics to be declared according to the declared intended uses mentioned in the annexes of this mandate. In order to take into account existing regulations on products where performance for one or more characteristics may not be required, the label should allow the manufacturer the application of the "No performance determined" case for that or those characteristics.

# **ANNEX 1**

FIELD OF APPLICATION

# ROAD CONSTRUCTION PRODUCTS

<u>Top</u>

### TO BE USED IN:

01/33 FLOOR BEDS (INCLUDING SUSPENDED GROUND FLOORS), ROADS AND OTHER TRAFFICKED AREAS

### 13/33 FLOOR FINISHES

FORM	MATERIALS	PRODUCTS FOR CONSIDERATION
formless	bitumen, polymers, admixtures	Bitumen:  pure bitumen, fluxed bitumen, bitumen emulsion, fluxed bitumen emulsion, cut-back bitumen, polymer modified bitumen, fluxed polymer modified bitumen, polymer modified bitumen emulsion, fluxed polymer modified bitumen emulsion
formless	asphalt, aggregates	Naturally occurring asphalt/bitumen
formless	bitumen, polymers, admixtures, aggregates	Bituminous mixtures (asphalt concrete including very soft asphalt and those for very thin layers, porous asphalt, mastic asphalt (gussasphalt), stone mastic asphalt, hot rolled asphalt). These asphalts may contain reclaimed asphalt.
formless	bitumen, polymers, admixtures, aggregates	Surface treatments: slurry for surfacing, microsurfacing, surface dressing
components	steel	Ancillary products :
	various	- dowels -joint fillers, joint sealants
flexible sheets, formless	bitumen, asphalt, resins, polymers, aggregates, stainless steel, aluminium, polyurethane, textiles	Bridge deck waterproofing products and kits (e.g. mastic asphalt, prefabricated membranes, preformed bituminous sheets, resins/polyurethane)

# **ANNEX 2**

TECHNICAL TERMS OF REFERENCE

Top

<u>Note</u>: not all of the characteristics shown in the following tables will be relevant for every product in a particular family or sub-family. CEN/CENELEC should select the subset of characteristics applicable to a particular product from the full set provided.

# ROAD CONSTRUCTION PRODUCTS

### TO BE USED IN:

01/33 FLOOR BEDS (INCLUDING SUSPENDED GROUND FLOORS), ROADS AND OTHER TRAFFICKED AREAS

13/33 FLOOR FINISHES

### FAMILY AND SUB-FAMILIES

# I) BITUMEN FOR ROAD CONSTRUCTION AND SURFACE TREATMENT OF ROADS

- naturally occurring asphalt/bitumen, pure bitumen, fluxed bitumen, bitumen emulsion, fluxed bitumen emulsion, cut-back bitumen, polymer modified bitumen, fluxed polymer modified bitumen, polymer modified bitumen emulsion, fluxed polymer modified bitumen emulsion

A - Pure l	A - Pure bitumen, polymer modified bitumen				
ER	Performance characteristics	Durability			
1 and 4	Hardness (including temperature dependence)				
	Resistance to flow / deformation (including temperature dependence)				
	Hardening or Setting ability	Y (Against			
	Cohesion	ageing, weathering,			
	Adhesion	oxidation, as relevant)			
2					
3	Release of polyaromatic carbons				
	Release of other dangerous substances*				
5					
6					

<sup>\*</sup> In particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

B - Fluxed bitumen, fluxed polymer modified bitumen, cut-back bitumen

ER	Performance characteristics	Durability
1 and 4	Viscosity	
	Water effect on binder adhesion	
	after stabilisation of the resting binder:	
	Hardness (including temperature dependence)  Resistance to flow / deformation (including temperature dependence)	
	Hardening or Setting ability	oxidation, as relevant)
	Cohesion	
	Adhesion	
2		
3	Release of dangerous substances*	
5		
6		

<sup>\*</sup> In particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

ER	Performance characteristics					
1 and 4	Viscosity					
	Water effect on binder adhesion					
	Breaking behaviour					
	after stabilisation of the resting binder:	Y (Against				
	Hardness (including temperature dependence)	ageing, weathering,				
	Resistance to flow / deformation (including temperature dependence)	oxidation, as relevant)				
	Cohesion					
	Adhesion					
2						
3	Release of dangerous substances*					
5						

\* In particular, those dangerous substances defined in Council Directive 76/769/EEC, as amended.

D - Naturally occurring asphalt / bitumen					
ER	Performance characteristics	Durability			
1 and 4	Bitumen content				
	Hardness (including temperature dependence)  Resistance to flow / deformation (including temperature dependence)	Y (Against ageing, weathering, oxidation, as relevant)			
2					
3					
5					
6					

## FAMILY AND SUB-FAMILIES

II) BITUMINOUS MIXTURES FOR ROAD CONSTRUCTION - with indication of type of compaction procedure, if required

Asphalt concrete including very soft asphalt and those for very thin layers, porous asphalt, mastic asphalt (gussasphalt), stone mastic asphalt, hot rolled asphalt. These asphalts may contain reclaimed asphalt.

ER	Performance characteristics	Durability
1 and 4	Adhesion of binder to aggregates	
	Stiffness	Y (Against ageing,
	Resistance to permanent deformation (e.g. rutting) (including temperature dependence	weathering, oxidation, wear,
	Resistance to fatigue / crack initiation	ravelling, chemicals, wear of studded tyres,
	Skid resistance	stripping, as relevant)
	Resistance to abrasion	
	Hydraulic conductivity	
2	Reaction to fire	
3		

5	Noise absorption	
6		

## FAMILY AND SUB-FAMILIES

## III) SURFACE TREATMENTS FOR ROADS

Slurry for surfacing, microsurfacing, surface dressing (which include aggregates)

ER	Performance characteristics	Durability
1 and 4	Adhesion of binder to aggregates	
	Resistance to flow / deformation (including temperature dependence)	
	Hardening or Setting ability  Cohesion  Skid resistance	
	Resistance to cracking	studded tyres, stripping, as relevant)
	Resistance to abrasion	
	Bond to substrate	
2	Reaction to fire	
3		
5	Noise absorption	
6		

### FAMILY AND SUB-FAMILIES

IV) BRIDGE DECK WATERPROOFING products and kits for bridges with or without an asphaltic layer

Waterproofing of a bridge is never provided by a single product but always by at least two products in combination.

- mastic asphalt

- prefabricated membranes
- preformed bituminous sheets
- resins / polyurethane (liquid applied)

ER	Performance characteristics	Durability
1 and 4	Watertightness	
	Resistance to deformation (including temperature dependence)	
	Maximum tensile strength and elongation (for membranes)	
	Bonding strength	
	Resistance to chloride ion penetration	Y (Against ageing,
	Joint strength	oil, chemicals, alkali,
	Resistance to dynamic actions	corrosion, weathering, deicing, as
	Capacity to penetrate pores of substratum (for resin and primer)	relevant)
	Capacity to bridge cracks (for concrete bridge decks)	
	Compatibility (including thickness depending on use)	
	Cold bending behaviour	
	Resistance to shear	
	Resistance to heat impact	
	Resistance to perforation	
2		
3		
5		
6		

	FAMILY AND SUB-FAMILIES
V) ANCILLARY PRODUCTS for	r concrete roads

A Danie	le.				
A - Dowe	:15				

ER	Performance characteristics	Durability
1	Shear strength	
	Bending strength	Y (Against
	Tensile strength	corrosion, as relevant)
2		
3		
4		
5		
6		

B - Joi	B - Joint fillers, joint sealants				
ER	Performance characteristics	Durability			
1	Bonding strength				
	Cohesion				
	Watertightness	Y (Against			
	Resistance to deformation (including temperature dependence)	chemicals, fuel, as relevant)			
2					
3					
4					
5					
6					

# **ANNEX 3**

## ATTESTATION OF CONFORMITY

Top

 $\underline{Note}$ : for products having more than one of the intended uses specified in the following families, the tasks for the approved body, derived from the relevant systems of attestation of conformity, are cumulative.

# **ROAD CONSTRUCTION PRODUCTS (1/2)**

Mandate M/124 Page 13 sur 16

### 1. Levels and classes for product performances

1.1 According to article 3.2 of the CPD and Clause 1.2.1 of the IDs, a classification of product performance has been identified as the means of expressing the range of requirement levels of the works in respect of **reaction to fire**.

Regarding reaction to fire, CEN/CENELEC are requested to follow the Commission Decision 94/611/EC [O.J. L 241 of September 1994] and make reference to the standard(s) to be prepared under Commission mandate to CEN/CENELEC "Horizontal complement to the mandates in respect of reaction to fire" in dealing with reaction to fire in the specific harmonised product standards to be developed under this mandate.

1.2 Reaction to fire is a risk for which the need for a classification system has been identified for the time being.

Further needs may be identified on the basis of differences specified in Article 3 (2) of the CPD, which are justified in conformity with Community law (IDs Clause 1.2.1).

Where for such needs it is recognised that a classification of product performance is the means of expressing the range of requirement levels of the works, the Commission will give the appropriate guidance or will request CEN/CENELEC to make the appropriate proposal through a modification to this mandate.

### 2. Systems of attestation of conformity

2.1 For the product(s) and intended use(s) listed below, CEN/CENELEC are requested to specify the following system (s) of attestation of conformity in the relevant harmonised standard(s):

Product	Intended use	Level/s or class/es	Attestation of conformity
			system
Bitumen	for road construction and surface treatment of roads	-	2+
Bituminous mixtures	for road construction and surface treatment of roads	-	2+
Surface treatments	for surface treatment of roads	-	2+
Bridge deck waterproofing products and kits	for bridge decks	-	2+
Ancillary products	for concrete roads	-	4

System 2+: See CPD Annex III.2.(ii), First possibility, including certification of the factory production control by an approved body on the basis of initial inspection of factory and of factory production control as well as of continuous surveillance assessment and approval of factory production control

System 4: See CPD Annex III.2.(ii), Third possibility

- 3. Conditions to be applied by CEN/CENELEC on the specifications of the attestation of conformity system
- 3.1 The specification for the system should be such that it can be implemented even where performance does not need to be determined for a certain characteristic, because at least one Member State has no legal requirement at all for such

characteristic [see the "no performance determined" case, clause 1.2.3 of the Interpretative Documents]. In those cases the verification of such a characteristic must not be imposed on the manufacturer if he does not wish to declare the performance of the product in that respect.

3.2 For products under system 2+, for the continuous surveillance, assessment and approval of the factory production control [see Annex III.1.g) of the CPD], only parameters related to the following characteristics shall be of the interest of the approved body:

### Bitumen:

- all characteristics relevant to ER 1, 3 and 4

### Bituminous mixtures:

- all characteristics relevant to ER 1 and 4

### Surface treatments:

- all characteristics relevant to ER 1 and 4

Bridge deck waterproofing products and kits:

- all characteristics relevant to ER 1 and 4
- 3.3 For products under system 2+, for the initial inspection of the factory and of the factory production control [see Annex III.1.f) of the CPD], parameters related to the above mentioned characteristics shall be of the interest of the approved body.

# **ROAD CONSTRUCTION PRODUCTS (2/2)**

- 1. Levels and classes for product performances
- 1.1 [ text as for family (1/2)]
- 1.2 [ text as for family (1/2)]
- 2. Systems of attestation of conformity
- 2.1 For the product(s) and intended use(s) listed below, CEN/CENELEC are requested to specify the following system (s) of attestation of conformity in the relevant harmonised standard(s):

Product	Intended use	Level/s	Attestation
		or class/es	of conformity
		(reaction to fire)	system (s)

Bituminous mixtures	for uses subject to reaction to fire regulations	(Afl, Bfl, Cfl)*	1		
Surface treatments					
		(Afl, Bfl, Cfl)**	3		
		Afl***, Dfl, Efl, Ffl	4		
System 1: See CPD Amex III.2.(i), without audit-testing of samples					
System 3: See CPD Annex III.2.(ii), Second possibility					
System 4: See CPD Annex III.2.(ii), Third possibility					

<sup>\*</sup> Materials for which the reaction to fire performance is susceptible to change during production (In general, those subject to chemical modification, e.g. fire retardants, or where changes of composition may lead to changes in reaction to fire performance)

## 3. Conditions to be applied by CEN/CENELEC on the specifications of the attestation of conformity system

- 3.1 The specification for the system should be such that it can be implemented even where performance does not need to be determined for a certain characteristic, because at least one Member State has no legal requirement at all for such characteristic [see Article 2.1 of the CPD and, where applicable, clause 1.2.3 of the Interpretative Documents]. In those cases the verification of such a characteristic must not be imposed on the manufacturer if he does not wish to declare the performance of the product in that respect.
- 3.2 For products under systems 1 and 3, regarding the initial type testing of the product [see Annex III.1.a) of the CPD], the task for the approved laboratory will be limited to the assessment of the following characteristics:
  - Euroclass characteristics for reaction to fire, as indicated in the Commission Decision 94/611/EC
- 3.3 For products under system 1, for the initial inspection of the factory and of the factory production control [see Annex III.1.f) of the CPD], and for the continuous surveillance, assessment and approval of the factory production control [see Annex III.1.g) of the Construction Products Directive], parameters related to the following characteristics shall be of the interest of the approved body:
  - Euroclass characteristics for reaction to fire, as indicated in the Commission Decision 94/611/EC

# **ANNEX 4**

DANGEROUS SUBSTANCES

<sup>\*\*</sup> Materials for which the reaction to fire performance is not susceptible to change during the production process

<sup>\*\*\*</sup> Materials of class A that according to the Decision 96/603 do not require to be tested for reaction to fire.

## ROAD CONSTRUCTION PRODUCTS

European Technical Specifications must be adopted taking into account the necessary legislation on substances classified as dangerous.

This results from the Interpretative Documents, where it is noted in the introduction note to all six Interpretative Documents, that:

"Concerning dangerous substances which are in construction products, classes and/or levels of performance to which technical specifications will refer, shall allow the levels of protection needed by the works to be guaranteed, taking into account the purpose of the works."

In addition, outside the scope of the Directive, writers of technical specifications must take into account legislation which affects material to be used for construction products, and which are regulated for reasons not related to the incorporation into the works of the construction products.

In order to permit technical specification writers to take into account the necessary legislation, a working document was elaborated by the Commission services (doc. CONSTRUCT 95/148 Rev.1 of January 4, 1996). Specification writers should use this document as a guide but must also take account of any other relevant legislation or dangerous substances which the working document does not yet include.

Top